





ACRYLIC LED NEON QUOTATION REQUEST FORM

Acrylic LED Neon Signs are custom-made with specific manufacturing parameters.

In order to provide you with a timely and accurate quote, we request the following information be provided to prevent errors and delays.

SIYLE		
Single Stroke Dual Stroke	Open Channel	Bulb Style
		,
DIRECTORD WADE		
<u>DIFFUSER TYPE</u> Rounded 12mm Frosted or Polished Clear Acrylic Top with 3mm Colored or White Opal Acrylic under the Diffuser.		
Rounded 12mm Frosted or Polished Clear Acrylic Top with	3mm Colored or White Opal Acryl	ic under the Diffuser.
12mm Polished Clear Acrylic Top	12mm Frosted Acrylic Top	
3mm Opal Acrylic Color Lit	Color Reference #	
<u>RETURNS</u>		
Painted 304# Stainless Steel	Brushed 304# Stainless Steel	
Painted Aluminum	PMS # etc	
LED'S		
Facelit with CE/UL Certified for indoor and outdoor applications.		
12v or 24v LED modules determined by factory at time of production.		
White (Specify Kelvin) Static Color	RGB	Pixel
MOUNTING		
Rear Screw Stud Mounts (1:1 Paper Template included)		
Mounted to Acrylic Backer Panel with Standoff Corner Pins		
Mounted to Painted Metal Backer Panel with Standoff	Corner Pins	Color Reference#
RGB/DMX CONTROL SYSTEMS		
Specific RGB/DMX control hardware to be determined based on customer/site requirements.		
Basic Programmable	Programmable & Network	able
POWER		

CE/UL Certified and Waterproof DC12V or 24V Power Supplies provided by Factory _____

ARTWORK REQUIREMENTS

Required File Types: - PDF from AutoCAD, Adobe Illustrator, or CorelDraw - .dwg

Keep the drawings simple, only linework is needed.

More often than not adding a color fill to the drawings, like in Figure 1, will result in broken and missing lines all over the imported drawing in AutoCAD.





You can still include color in the drawing if it is only the lines that are colored. Figure 3 shows an example of a PDF file that has all the appropriate linework and imports well into AutoCAD (Figure 4.)











Dual Stroke Examples

Channeled Neon Examples